

# **M Series 3**

# Maximum security. Maximum potential. Maximum results.

Delivering a truly intuitive and collaborative experience, M Series 3 is an interactive screen with unlimited possibilities. Combines high-quality design, functionality, durability, native screen sharing and 4K resolution.



Software included at no extra cost



LYNX Whiteboard is a free-to-use lesson building app, enabling student collaboration. The most dynamic, intuitive user experience of any whiteboard



#### Software included at no extra cost





Your IT team can control, update and troubleshoot a fleet of Clevertouch screens without entering the classroom, ensuring your teachers always have the latest versions of apps and software when teaching.



Any device can download the Clevershare app and connect instantly by typing in the code on the Clevertouch screen. Clevershare App is free to download and compatible with Android, Windows, iOS, and Chrome devices.

## **Key Features**



Our patented Super Glide Touch technology offers the most fluid writing experience



Remote management MDM



Never run out of space with our infinite whiteboard



4GB RAM 32GB ROM



easy with a huge selection of



M Series is powered by Android 11



LYNX Whiteboarding made pen & art tools to use



Clevershare screen mirroring

allows you to share images,

video and audio

Cyber Essentials compliant



Connect your Cloud accounts to work from anywhere



Huge connectivity including one of the latest USB-C ports with charging ability



2 x high powered 16W speakers for crystal clear sound quality

## M Series 3 Specifications

## Display

Diagonal Size  65" 4K, 75" 4K, 86" 4K  Screen Type  TFT LCD - Direct LED Backlight  Aspect Ratio  16:9  Display Colours  1.07 Billion (10 bit)  Resolution  4K UHD (3840x2160 @60Hz)  Response Time  5ms  Refresh Rate  60Hz  LCD Viewing Angle  178°  Brightness  450 cd/m2  Contrast Ratio  65" 4000:1 75" 5000:1 86" 4000:1 75" 6000:1 75" 6000:1 86" 6000:1 75" 6000:1 86" 6000:1  Glass Hardness  Glass Thickness  Glass Type  Low Parallax 1mm Air Gap - Heat tempered  Main Board  Amlogic T982 (SoC)  Life of Screen  50,000 Hours  NTSC  65" 72% 75" 72% 86" 68%		
Aspect Ratio         16:9           Display Colours         1.07 Billion (10 bit)           Resolution         4K UHD (3840x2160 @60Hz)           Response Time         5ms           Refresh Rate         60Hz           LCD Viewing Angle         178°           Brightness         450 cd/m2           Contrast Ratio         65" 4000:1 75" 5000:1 86" 4000:1 75" 6000:1 86" 6000:1           Dynamic Contrast Ratio         65" 65" 6000:1 86" 6000:1 86" 6000:1           Glass Hardness         Tempered Glass - Mohs Level 7           Glass Thickness         3mm           Glass Type         Low Parallax 1mm Air Gap - Heat tempered           Main Board         Amlogic T982 (SoC)           Life of Screen         50,000 Hours           NTSC         65" 72% 75" 72%	Diagonal Size	65" 4K, 75" 4K, 86" 4K
Display Colours         1.07 Billion (10 bit)           Resolution         4K UHD (3840x2160 @60Hz)           Response Time         5ms           Refresh Rate         60Hz           LCD Viewing Angle         178°           Brightness         450 cd/m2           Contrast Ratio         65" 4000:1 75" 5000:1 86" 4000:1 86" 6000:1 86" 6000:1           Dynamic Contrast Ratio         75" 6000:1 86" 6000:1 86" 6000:1           Glass Hardness         Tempered Glass - Mohs Level 7           Glass Thickness         3mm           Glass Type         Low Parallax 1mm Air Gap - Heat tempered           Main Board         Amlogic T982 (SoC)           Life of Screen         50,000 Hours           NTSC         75" 72% 75" 72%	Screen Type	TFT LCD - Direct LED Backlight
Resolution         4K UHD (3840x2160 @60Hz)           Response Time         5ms           Refresh Rate         60Hz           LCD Viewing Angle         178°           Brightness         450 cd/m2           Contrast Ratio         65" 4000:1 75" 5000:1 86" 4000:1           Dynamic Contrast Ratio         65" 6000:1 75" 6000:1 86" 6000:1           Glass Hardness         Tempered Glass - Mohs Level 7           Glass Thickness         3mm           Glass Type         Low Parallax 1mm Air Gap - Heat tempered           Main Board         Amlogic T982 (SoC)           Life of Screen         50,000 Hours           NTSC         75" 72%	Aspect Ratio	16:9
Response Time         5ms           Refresh Rate         60Hz           LCD Viewing Angle         178°           Brightness         450 cd/m2           Contrast Ratio         65" 4000:1 75" 5000:1 86" 4000:1           Dynamic Contrast Ratio         65" 6600:1 75" 6000:1 86" 6000:1           Glass Hardness         Tempered Glass - Mohs Level 7           Glass Thickness         3mm           Glass Type         Low Parallax 1mm Air Gap - Heat tempered           Main Board         Amlogic T982 (SoC)           Life of Screen         50,000 Hours           NTSC         65" 72% 75" 72%	Display Colours	1.07 Billion (10 bit)
Refresh Rate         60Hz           LCD Viewing Angle         178°           Brightness         450 cd/m2           Contrast Ratio         65" 4000:1 75" 5000:1 86" 4000:1           Bown Contrast Ratio         65" 6000:1 75" 6000:1 86" 6000:1           Glass Hardness         Tempered Glass - Mohs Level 7           Glass Thickness         3mm           Glass Type         Low Parallax 1mm Air Gap - Heat tempered           Main Board         Amlogic T982 (SoC)           Life of Screen         50,000 Hours           NTSC         75" 72%	Resolution	4K UHD (3840x2160 @60Hz)
LCD Viewing Angle	Response Time	5ms
Brightness	Refresh Rate	60Hz
Contrast Ratio  65" 4000:1 75" 5000:1 86" 4000:1  Dynamic Contrast Ratio  65" 6000:1 75" 6000:1 86" 6000:1 86" 6000:1  Glass Hardness  Tempered Glass - Mohs Level 7  Glass Thickness  3mm  Glass Type  Low Parallax 1mm Air Gap - Heat tempered Main Board  Amlogic T982 (SoC)  Life of Screen  50,000 Hours  NTSC  65" 72% 75" 72%	LCD Viewing Angle	178°
Contrast Ratio         75" 5000:1 86" 4000:1           Dynamic Contrast Ratio         65" 6000:1 75" 6000:1 86" 6000:1           Glass Hardness         Tempered Glass - Mohs Level 7           Glass Thickness         3mm           Glass Type         Low Parallax 1mm Air Gap - Heat tempered           Main Board         Amlogic T982 (SoC)           Life of Screen         50,000 Hours           NTSC         75" 72%	Brightness	450 cd/m2
Dynamic Contrast Ratio  75" 6000:1 86" 6000:1  Glass Hardness  Tempered Glass - Mohs Level 7  Glass Thickness  3mm  Glass Type  Low Parallax 1mm Air Gap - Heat tempered  Main Board  Amlogic T982 (SoC)  Life of Screen  50,000 Hours  NTSC  65" 72% 75" 72%	Contrast Ratio	75" 5000:1
Glass Thickness  Glass Type  Low Parallax 1mm Air Gap - Heat tempered  Main Board  Amlogic T982 (SoC)  Life of Screen  50,000 Hours  NTSC  65" 72% 75" 72%	Dynamic Contrast Ratio	75" 6000:1
Glass Type  Low Parallax 1mm Air Gap - Heat tempered  Main Board  Amlogic T982 (SoC)  Life of Screen  50,000 Hours  NTSC  65" 72%  75" 72%	Glass Hardness	Tempered Glass - Mohs Level 7
Main Board         Amlogic T982 (SoC)           Life of Screen         50,000 Hours           NTSC         65" 72% 75" 72%	Glass Thickness	3mm
Life of Screen 50,000 Hours  65" 72%  NTSC 75" 72%	Glass Type	Low Parallax 1mm Air Gap - Heat tempered
NTSC 65" 72% 75" 72%	Main Board	Amlogic T982 (SoC)
NTSC 75" 72%	Life of Screen	50,000 Hours
	NTSC	75" 72%

## Interactivity

Writing Technology	High Precision IR Technology	
<b>Continuous Touch Points</b>	20	
Touch Resolution	32768x32768px	
Response Time	≤5ms	
Touch Accuracy	1mm	
Minimum Object Size	3mm	
Touch Tool	Finger, passive pen, opaque objects	
Simultaneous Writing	Yes	
Ink In Tools	Yes - Lynx	
Pens Included	2	
Pen Type	Dual Recognition Stylus   Super Cool Stylus	
Pen Holder	Integrated magnetic pen holders	
Pen Tip Diameter	3mm/7mm	
Pen & Touch Differentiation	Yes	
Pen Identities	2	
Palm Rejection	Yes	
Annotation Over Any Source	Yes	
Classroom Essential Apps	Includes Whiteboard, Annotate, Timer, Media Players, Browser, PDF Reader, Screen Record, Spinner, Voting, Maths Tools	
Compatibility*	Windows 10, Linux, Mac, Android, Chrome	
Tracking Rate	≥1m/s	
Scan Rate	200Hz	
Gestures & Edge Swipes	Windows Supported, OSX With additional Driver	

## Connectivity

OPS Slot	1 - Intel Spec 80Pin	
HDMI In	3	
HDMI Out	1	
USB-A 2.0	1	
USB Touch (type B)	2	
USB A 3.0 (Faster Data Transfer)	4	
USB C (Video, Audio & Touch)	1 (supports 65W charging)	
LAN In (RJ45)	1 GB	
LAN Out (RJ45)	1	
RS-232	1	
Wake-on-Lan	Yes	
Wireless Adapter 2.0 + WAP	Yes	
Clevertouch WiFi Module	Yes	
Bluetooth	Yes 5.0	
Displayport In	No	
VGA In	1	
Audio In	1	
Optical Out	1	
Headphone	1 (3.5mm)	
Total touch out ports	2	
NFC Reader / Writer	Optional Extra	
Camera	Optional Extra	
Proximity Sensor	No	
WiFi	IEEE 802.11a/b/g/n/ac/ax with 2 × 2 MIMO (hotspot only) (both 2.4 and 5 GHz bands)	
WiFi Speed	Capable of speeds up to 433Mbps	

## Computing

Operating System	Android 11
System Version	LUX 11
RAM	4GB
Internal Storage	32GB
CPU	Quad Core A55
GPU	Mali G52MP2
Android Resolution	4K
Android Module Slot	No
System Architecture	32-bit
Integrated LUX UI	Yes

#### Power

Power Requirements	100-240V ~ 50/60Hz
Power Consumption (Standby)	≤0.5W
Ultra Quiet Fanless Design	Yes
Power Consumption	65" 178 Watts 75" 183 Watts 86" 195 Watts

#### M Series 3 Specifications

#### Audio

Dual Front Facing, Bass Enhanced Speakers	2 x 16W
Audio Out	Yes
SPDIF / Fibre	Yes
Sound Channel	2
Line	No
Super Wide Sound	No

#### Operating & Storage Environment

Operating Temperature	0° to 40°
Storage Temperature	-20° to 60°
Operating Humidity	10% to 90% RH
Storage Humidity	10% to 90% RH
Altitude	Below 5000 metres

#### **Physical Spec**

Panel Dimensions	65" 1489x906x87mm 75" 1709x1013x88mm 86" 1957x1168x88mm
Packed Dimensions	65" 1628x208x1005mm 75" 1863x225x1148mm 86" 2110x225x1291mm
Net Weight	65" 35.9kg 75" 47.75kg 86" 62.9kg
Packed Weight	65" 46.25kg 75" 61.9kg 86" 80.6kg
VESA Mount Point	65" 600x400mm 75" 800x400mm 86" 800x600mm

## M Series 3 Built-In Features

LYNX™ App With Online Lesson Planning	Yes
Clevershare™ Mirroring Any Device To The Board	Free for the life of the screen (touch back)
Integrated Personalised Accounts Profiles	Yes
Cloud Account Access	OneDrive, Google Drive
Whiteboard Annotation	Yes
Email Out Direct From Touchscreen	Yes
Scan QR Code For Saving Work	Yes
Remote Management Of Touchscreens (MDM)	Yes - Five year license

#### Warranty

Warranty term and upgrade options vary by region. Contact your local reseller or distributor for information

#### Compliance & Certification

<b>Regulatory Certification</b> CE, FCC, UL, Energy Star & EEC
--











#### Inside your Clevertouch Box

#### What's In The Box

- (1) Clevertouch M Series 3
- (1) 1.5M Length HDMI Cable
- (1) 3M Length USB cable (A-B)
- (1) 1.5M USBC Cable
- (1) 3M Regional Power Cable
- (1) Remote Control
- (2) Batteries for Remote Control
- (2) Dual Recognition Stylus
- (1) User Guide
- (1) Quick Install Guide
- (1) Clevertouch WiFi Module

#### Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.

© 2021 Clevertouch. All rights reserved. Sahara Presentations Systems PLC. is part of the Boxlight group of companies, and the owner of trademarks in several global jurisdictions including but not limited to Clevertouch, the Clevertouch logo, UX Pro, IMPACT™, IMPACT Plus™, Impact MAX, CleverLive, LUX, Lynx, CleverMessage, Cleverstore and Clevershare. All third-party trademarks (including logos and icons) referenced by Clevertouch remain the property of their respective owners. Unless specifically identified as such, Clevertouch's use of third-party trademarks does not indicate any relationship, sponsorship, or endorsement between Clevertouch and the owners of these trademarks. Applicable Terms and Conditions for warranty and support available at clevertouch.com/about/warranty. All weights and dimensions are approximate. Product specifications are subject to change without notice. Clevertouch.com.