BenQ Education

RE9803

Essential Series











Eye-care solution can function by activating eye-care mode. BenQ's Eye-care technology spent in front of the display, helping you create the best experience for you and your



The **EZWrite 6** software has features, making the cloud straightforward to use. Teachers can share their work from the interactive display, using their own devices, without installing any software. With this tool, hybrid learning becomes



BenQ's **Device Management Solution (DMS)** allows IT teams

Account Management System (AMS) provides personalised workspaces including access to cloud files and tailored

Panel				
Panel	Panel	Screen size		98"
Panel		Resolution		4K UHD 3840 x 2160
Panel		Brightness (typ.)		350 nits
Panel Viewing angle (H/V) 178° Response time (Θ-t-G) 8 ms 6000 Backlight life (hrs) 500000 Panel surface AG, Haze 25% Operating hours 18 / 7 Orientation Landscape Platform solution Storage 32 GB Storage 32 GB Power 100 V~240 V, 50 -60 Hz A c power supply 100 V~240 V, 50 -60 Hz Power Maximum (W/h) 570 AC power switch Yes Wake up LAN / HDMI / VGA Touch Technology IR Mumber of touch points up to 40 Interface USB Type B x 2 Glass Tempered glass 4.0 mm AG coating Yes Ladd but just (TU't certified) Yes ClassroomCareenee Eye-Care Solution - Flicker-Free & Low Buc Light (TU't certified) Yes ClassroomCareenee Eye-Care Solution - Flicker-Free & Low Buc Light (TU't certified) No ClassroomCareenee Free (Tu'x & SIA certified) No<		Contrast ratio (typ.)		1200:1
Response time G-t-G)		Dynamic contrast ratio		30.000 : 1
Backlight life (hrs)		Viewing angle (H/V)		178°
Panel surface		Response time (G-t-G)		8 ms
Operating hours		Backlight life (hrs)		50000
		Panel surface		AG, Haze 25%
Platform solution Storage		Operating hours		18 / 7
Platform solution		Orientation		Landscape
Power Power supply 100V~240V, 50-60Hz		System memory		4GB
Power Pow		Storage		32GB
Power Pow		os		Android 11.0
Power		Power supply		100V~240V, 50-60Hz
Power		_	Maximum (W/h)	570
Standby mode (W/h)			Typical (W/h)	183
Touch Touch Technology IR IR IR IR IR IR IR I			Standby mode (W/h)	<0.5
Technology		AC power switch		Yes
Number of touch points Up to 40 Interface				LAN / HDMI / VGA
Interface	Touch	Technology		IR
Tempered glass		Number of touch points		up to 40
Glass Hardness 9H AG coating Yes Eye-Care Solution - Flicker-Free & Low Blue Light (TÜV certified) Yes ClassroomCare® Technology Eye-Care Solution - Flicker-Free & Low Blue Light (TÜV certified) No Germ-Resistant Screen (TÜV & SIAA certified) No Operation temperature 0°C ~ 40°C Operation temperature 0°C ~ 40°C Operating humidity 10% ~ 90% RH non-condensing Energy Star 8.0 Certified Upperation temperature VGA x1, HDMI 2.0 x3, Audio (3.5 mm) x 1 USB Type Ax7 (2.0 x2/32 x5), Type Bx2 (2.0 x1/3.0 x1), Type Cx1 (3.1) USB Type Ax7 (2.0 x2/32 x5), Type Bx2 (2.0 x1/3.0 x1), Type Cx1 (3.1) X1 RS232 x1 10/100 / 1000 Mbps (Android) Remote controller x1 16W x 2 (frontal) Audio Dolby Audio No X244.7 x 1323.2 x 89.5 mm <		Interface		USB Type B x 2
AG coating	Glass	Tempered glass		4.0 mm
ClassroomCare® Technology		Hardness		9H
Low Blue Light (TÜV certified)		AG coating		Yes
Air-Quality Sensor No				Yes
Cerm-Resistant Screen (TÜV & SIAA certified) No		Air-Quality Sensor		No
Environment Operating humidity Energy efficiency Energy Star 8.0 Certified				No
Energy efficiency	Environment	Operation temperature		0°C ~ 40°C
Input		Operating humidity		10% ~ 90% RH non-condensing
Connectivity HDMI 2.0 x 1, Audio (3.5 mm) x 1 USB Type A x 7 (2.0 x 2 / 3.2 x 5), Type B x 2 (2.0 x 1 / 3.0 x 1), Type C x 1 (3.1) RS232 x 1 RJ45 (LAN) 10 / 100 / 1000 Mbps (Android) Remote controller x 1 Built-in speaker 16W x 2 (frontal) No Array microphores No Screen dimension (mm) 2244.7 x 1323.2 x 89.5 mm Weight (kg) 98.5 Gross weight 124.2 Bezel width (mm) 26.7 46.1 26.7 26.7 Wall mounting (VESA) (screw type / max. length) VESA 800 x 600 mm (4x M8 x 25L) Wall mount kit Included OPS slot Yes No Pen holder Yes (magnetic)		Energy efficiency		Energy Star 8.0 Certified
Connectivity Type A x 7 (2.0 x 2 / 3.2 x 5), Type B x 2 (2.0 x 1 / 3.0 x 1), Type C x 1 (3.1) RS232 x 1 RJ45 (LAN) 10 / 100 / 1000 Mbps (Android) Remote controller x 1 Built-in speaker 16W x 2 (frontal) No Array microphones No Screen dimension (mm) 2244.7 x 1323.2 x 89.5 mm Weight (kg) 98.5 Gross weight 124.2 Bezel width (mm) 26.7 46.1 26.7 26.7 Wall mounting (VESA) (screw type / max. length) (4 × M8 × 25L) Wall mount kit Included OPS slot Yes No Pen holder Yes (magnetic)	Connectivity	Input		VGA x 1, HDMI 2.0 x 3, Audio (3.5 mm) x 1
RS232		Output		HDMI 2.0 x 1, Audio (3.5 mm) x 1
RJ45 (LAN) 10 / 100 / 1000 Mbps (Android)		USB		
Remote controller		RS232		x 1
Built-in speaker 16W x 2 (frontal) Dolby Audio No Array microphores No Screen dimension (mm) 2244.7 x 1323.2 x 89.5 mm Weight (kg) Net weight 98.5 Gross weight 124.2 Bezel width (mm) 26.7 46.1 26.7 26.7 Wall mounting (VESA) (screw type / max. length) VESA 800 x 600 mm (4 x M8 x 25L) Wall mount kit Included OPS slot Yes NFC sensor No Pen holder Yes (magnetic)		` '		10 / 100 / 1000 Mbps (Android)
Audio Dolby Audio No Array microphones No Screen dimension (mm) 2244.7 x 1323.2 x 89.5 mm Weight (kg) Net weight 98.5 Gross weight 124.2 Bezel width (mm) 26.7 46.1 26.7 26.7 Wall mounting (VESA) (screw type / max. length) VESA 800 x 600 mm (4 x M8 x 25L) Wall mount kit Included OPS slot Yes NFC sensor No Pen holder Yes (magnetic)				
Array microphones No		•		. ,
Screen dimension (mm) 2244.7 x 1323.2 x 89.5 mm	Audio	•		
Weight (kg)				1.19
Weight (kg) Gross weight 124.2	Mechanical	Screen dimens	` ,	
Mechanical Bezel width (mm) 26.7 46.1 26.7 26.		- ' ' '		
Mechanical Wall mounting (VESA) (screw type / max. length) VESA 800 × 600 mm (4 × M8 × 25L) Wall mount kit Included OPS slot Yes NFC sensor No Pen holder Yes (magnetic)				
(screw type / max. length)		, ,		
Wall mount kit Included OPS slot Yes NFC sensor No Pen holder Yes (magnetic)				
OPS slot Yes NFC sensor No Pen holder Yes (magnetic)				,
NFC sensor No Pen holder Yes (magnetic)				
Pen holder Yes (magnetic)				
1 (13 11)				
vvariality 3-year warranty on-site exchange				, , ,
	warranty 5-year warranty on-site exchange			



EZWrite 6

Save lessons in editable whiteboard files (IWB) with Cloud Whiteboarding. Google Classroom is integrated with EZWrite WEB.



InstaShare 2



X-Sign Broadcast

Announcement system with cross-campus communication. Send visual alerts, warnings, videos to all or one specific device.



ΔMS



DMS

FRONT I/O



POWER



REMOTE CONTROL SENSOR





AMBIENT LIGHT SENSOR



USB TYPE-C



HDMI









воттом і/о









S/PDIF OUT

VGA

SIDE I/O









USB 3.0






HDMI




HDMI OUT



USB 2.0





Benq

