

ZU606Te

High brightness professional laser projector



- **Bright WUXGA laser projector - 6,300 lumens**
- **30,000 hours maintenance-free laser light source at full brightness**
- **4K and HDR compatible**
- **HDBaseT Connectivity**

Introducing the ZU606Te, the smallest projector in its class. At 6,300 lumens with 4K and HDR compatibility, the ZU606Te is a low maintenance projector with extremely long-life laser technology also including vertical lens shift and built-in 10W speakers.

Suitable for a wide variety of applications, this unit is perfect for anywhere that requires a clean bright image including large venues, classrooms/lecture theatre's, museums and houses of worship.

The added control flexibility of HDBaseT and LAN make this projector an affordable fit and forget solution.

Specifications

EAN: 5055387664050, Colour: white

EAN: 5055387664333, Colour: Black



Display/image	
Display technology	DLP™
Resolution	WUXGA (1920x1200)
Brightness	6,300 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9, 16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Has vertical auto keystone correction	Yes
Displayable colours (millions)	1073.4
Horizontal scan rate	15.375~91.146 Khz
Vertical scan rate	24~ 85 Hz (120Hz for 3D)Hz
Uniformity	85%
Screen size	0.8m ~ 7.67m (31.5" ~ 301.8") diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.2:1 ~ 1.92:1
Projection distance (m)	1.3m - 7.8m
Zoom	1.6
Zoom type	Manual
Focal length (mm)	11.66
Lens shift	Vertical -100 ~ 120%
Native offset	100%
Lens shift	Yes - {{downloads_link}}
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 2 x VGA, 1 x Composite video, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x S-Video Outputs 1 x VGA, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x RS232, 1 x 12V trigger, 1 x RJ45
LAN - wireless networking	No
General	
Noise level (typical)	32dB
Noise level (max)	34dB
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(24/50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6x
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
Operating conditions	Sea Level to 10,000 feet (@23°C); manual switch to high altitude mode @5000 feet & above
Remote control	Backlit ProAV remote
Heat dissipation	1,521BTU/hour
Speaker count	2
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	HDCast Pro
Networking	
LAN - control	Yes
LAN - wireless networking	No
LAN	Yes
Power	
Power supply	100V ~ 240V ± 10%, 50-60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	211W
Power consumption (max)	446W
Weight and dimensions	
Dimensions (W x D x H) mm	374 x 302 x 117
Gross weight	7.5 kg
Net weight	3.9 kg



Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be the trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 23012023015611