### **EB-PU2216B**



# The EB-PU2216B is a high lumens 3LCD projector that's ultralightweight and compact.

The EB-PU2216B offers users significant advantages including much reduced size and weight, easier installation and set-up, simplified maintenance and great image quality. This ultra-lightweight, compact laser projector has been designed for use in large auditoriums, live events, concerts, conference rooms where it delivers high-impact immersive experiences.

#### Compact and lightweight

The reduced weight and size means the projector is easier to store, transport and install, saving on warehouse space as well as labour and delivery costs.

#### Outstanding image quality

This high lumens, 3LCD projector offers WUXGA resolution with 4K enhancement and HDR for rich textures and sharper images.

#### Flexibility

The EB-PU2216B's functionality enables simple installation, stacking, lens flexibility and control. It includes in-built processing for PC-free stacking which means two supported projectors can be stacked to double the brightness without the need for external computerware.

#### Reliability

Includes improved dustproofing as the hermetically sealed optical engine, and laser light source unit, prevent dust contamination to ensure enhanced durability.

#### **DATASHEET / BROCHURE**































## KEY FEATURES

- Ultra-lightweight and compact Easy to store, transport and install
- Stunning image displays
   16,000lm, 4K Enhancement technology,
   WUXGA resolution
- Easy to use Simple installation, stacking, lens flexibility and control
- Fit-and-forget reliability
   Enhanced dustproof construction. IP5x certified
- Environmental benefits
  Lower power consumption, reduced packaging, reduced weight





#### PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology
LCD Panel 1.03 inch with C2 Fine

IMAGE

Color Light Output 16,000 Lumen - 11,200 Lumen (economy) In accordance with IDMS15.4

White Light Output 16,000 Lumen - 11,200 Lumen (economy) In accordance with ISO 21118:2020

Resolution WUXGA
High Definition 4K enhancement
Aspect Ratio 16:10

Contrast Ratio Over 2,500,000 : 1
Native Contrast 2,000 : 1

Light source Laser

Laser Light source 20,000 hours Durability High, 30,000 hours Durability Eco

Colour Video Processing 10 Bits

Colour Reproduction Upto 1.07 billion colours

HDR support HDR10, HLG

OPTICAL

Throw Ratio 0.35 - 7.41:1

Zoom Motorized, Factor: 1 - 1.6

Lens varies by lens

Lens Shift Motorized - Vertical ± 60 %, horizontal ± 18 %, varies by lens

Lens position memory 10 positions

Screen Size 60 inches - 1,000 inches, varies by lens

Projection Distance Wide )varies by lens
Projection Distance Tele )varies by lens
Projection Lens F Number varies by lens
Projection Lens Focal Length varies by lens
Projection Lens Focus Motorized
Interchangeable Lens Yes
Standard Lens Not included
Mechanical shutter Yes

CONNECTIVITY

Interfaces USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet Interface (1000 Base-T/ 100-

Base TX/10-Base-T), VGA in, DVI in, HDMI in, HDBaseT, Jack plug out, 3G-SDI Input, 3G-SDI Output, Wireless LAN IEEE 802.11a/b/g/n (optional), Near Field Communication (NFC), USB

content playback, Remote

Network Protocol HTTPS, IPv6, SNMP, ESC/VP.net, PJLink

ADVANCED FEATURES

Security Kensington lock, Security bar, Password lock, Wireless LAN unit lock, Wireless LAN security,

Password protection

Other features 21:9 aspect ratio support, 4K enhancement, Auto Power On, Auto source search, Direct Power

on/off, Edge Blending, Lens position memory, Long light source life, OSD copy function, Point correction, Power on button, Quick Corner, Schedule Function, Split-Screen-Function, Super

resolution, Web Control, Web Remote, iProjection App

Video Color Modes Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709

Projector control via: AMX, Crestron, Extron

Sealed Light Source Module Yes, IP5X rated
Sealed Optical Engine Yes, IP5X rated

#### **EB-PU2216B**

#### WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- User manual
- Lens connector cap
- Warranty document





#### PRODUCT SPECIFICATIONS

**GENERAL** 

Power consumption 1,083 Watt, 773 Watt (economy), 0.4 Watt (standby), On mode power consumption as defined

in JBMS-84 902 Watt

Heat Dissipation 3,682 BTU/hour (max)

Supply Voltage AC 200 V - 240 V, 50 Hz - 60 Hz

Product dimensions 586 x 492 x 218 mm (Width x Depth x Height)

Product weight 24.2 kg

Noise Level Normal: 38 dB (A) - Economy: 34 dB (A)

Supported Temperature Storage -10° C - 60° C

Supported Humidity Operation 20% - 80%, Storage 10% - 90%

Included Software Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Config Tool, Epson

Projector Content Manager, Epson Projector Management, Epson Projector Professional Tool

Options Camera module, Ceiling mount, Wireless LAN unit

Positioning Ceiling Mounted, Desktop, Flying Frame

Colour Black

OTHER

Warranty 36 months Carry in

Optional warranty extension available

#### **EB-PU2216B**

#### WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- User manual
- Lens connector cap
- Warranty document



#### **OPTIONAL ACCESSORIES**

 Adapter - ELPAP11 Wireless LAN (5GHz) V12H005A01

• Camera Unit - ELPEC01

V12HA46010

• Ceiling Mount - ELPMB68

V12H006AE0

• Extension Pole - ELPMB70 - For ELPMB68

V12H006AG0

• Truss Adaptor - ELPMB71 - For ELPMB68

V12H006AH0

• Stacking Frame - ELPMB59 - EB-PU2200 Series (EVO)

V12H996B59

#### **OPTIONAL LENSES**

 Lens - ELPLL08 - Long throw - EB-PU Series V12H004L08

 Lens - ELPLM10 - Mid throw 3 - EB-PU Series V12H004M0A

 Lens - ELPLM11 - Mid throw 4 - EB-PU Series V12H004M0B

 Lens - ELPLM15 - Mid throw - EB-PU Series V12H004M0F

 Lens - ELPLU03S - Short throw off axis 1 - EB-PU Series V12H004UA3

 Lens - ELPLU04 - Short throw off axis 2 - EB-PU Series V12H004U04

Lens - ELPLW06 - Wide zoom 2 - EB-PU Series
 V12H004W06

 Lens - ELPLW08 - Wide throw - EB-PU2000 Series V12H004W08

 Lens - ELPLX02S - UST - EB-PU2000 Series V12H004X0B

 Lens - ELPLX02WS - UST - EB-PU2000 Series V12H004Y0B

#### **LOGISTICS INFORMATION**

SKU	V11HA67840
EAN code	8715946703237
Country of Origin	China
Layer	1 Units
Layer Block	1 Units



For more information please contact:

Home users: 0343 90 37766 Business users\*: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus \* 10p per minute plus network extras. Web: www.epson.co.uk www.epson.ie



**EB-PU2216B**